

NO.	National Code	National Code	Item Description	Unit	Ottobock Code	Ottobock Discription	Qty. 2021 (pcs)	Unit Price USD	Total price UFS D
1.	ALL-RE18-197	Add	surform holder(file), used as holder for the above surform.	pcs	716Y5	Surform Rasp Holder	452	20	9040
2.	ALL-RE18-199	Add	surform holder(file), used as holder for the above surform.	pcs	716R1	Surfrm Round Rasp	529	20	10580
3.	ALL-RE18-201	Add	Surform holder(file), used as holder for the above surform.	pcs	716Y5	Surform Rasp Holder	278	20	5560
4.	ALL-RE00-203	T 8	Sanding drum, made of rubber, service part for grinding machine to pull onto router machine shaft, outside diameter 72.5 mm, length 200 mm.	pcs	749F6	Sanding Drum	198 + 2pcs FOC	25	4950
5.	ALL-RE00-204	T 9	Sanding sleeve used with the sanding drum above(T8), outside diameter 73mm, length 200 mm, grit 40.	pcs	749Y8=73X200X40	Sanding Sleeve for 749F6+749F6=T	709 + 8 pcs FOC	7	4963
6.	ALL-RE00-205	T 10	Sanding sleeve used with the sanding drum above(T8), outside diameter 73mm, length 200 mm, grit 80.	pcs	749Y8=73X200X80	Sanding Sleeve for 749F6+749F6=T	437 + 5pcs FOC	6	2622
7.	ALL-RE00-206	T 11	Sanding drum, service part for grinding machine, grinder made of rubber with metallic core, thread M 16, outside diameter 45 mm, length 70 mm.	pcs	749Z7=M16X45	Sanding Drum	30+ 1pcs FOC	110	3300
8.	ALL-RE00-207	T 12	Sanding drum, service part for grinding machine, grinder made of rubber with metallic core, thread M 16, outside diameter 60 mm, length 70 mm.	pcs	749Z7=M16X60	Sanding Drum	30+ 1pcs FOC	135	4050
9.	ALL-RE00-208	T 13	Sanding sleeve, used for sanding drum in item T11, outside diameter 45 mm, length 70, grit 40.	pcs	749Y16=A45	Sand sleeve f. 749z7 width 70mm Grit 40	182 + 2pcs FOC	4	728
10	ALL-RE00-209	T 14	Sanding sleeve, used for sanding drum in item T12, outside diameter 60 mm, length 70, grit 80.	Pcs	749Y16=A60	Sand sleeve f. 749z7 width 70mm Grit 40	157 + 2pcs FOC	4	628
11	ALL-RE00-210	T 15	Sanding drum, service part for grinding machine, grinder made of rubber with metallic core, thread M 16, outside diameter 25 mm, length 45 mm.	pcs	749Z8=M16X25	Sanding Drum	71	188	13348
12	ALL-RE00-211	T 17	Sanding sleeve, used for sanding drum in item T15, grit 40.	pcs	749Y22=A25	Sanding Sleeve	291	4	1164
13	ALL-RE00-212	T 18	Sanding drum, service part for grinding machine, drum made of rubber(cap or arbor shap) with metallic core, thread M 16, outside diameter 45 mm, length70 mm.	pcs	749F8 M16X45	OTTO BOCK Round End Sanding Drum	31+ 1pcs FOC	140	4340
14	ALL-RE00-213	T 19	Sanding drum, service part for grinding machine, drum made of rubber(cap or arbor shap) with metallic core, thread M 16, outside diameter (60-65 mm), length 90mm.	pcs	749F8=M16X65	OTTO BOCK Round End Sanding Drum	32+ 1pcs FOC	150	4800

15	ALL-RE00-214	T 20	Sanding sleeve, used for sanding drum in item T18, grit 40.	pcs	749Y10=A45	Sanding Sleeve 40 GRIT 6 Pack	53 pack + 1 pack FO C	60	3180
16	ALL-RE00-215	T 21	Sanding sleeve, used for sanding drum in item T19, grit 40.	pcs	749Y10=A65	Sanding Sleeve 40 GRIT 6 Pack	51 pack + 1 pack FO C	80	4080
17	ALL-RE00-217	T 43	Hot air gun , technical data : 1- power/ 220-230 V. 2- temperature range 20-700 C . 3-round nozzle.	pcs	756E2	Hot air gun ,technical data : 1- power/ 220-230 V.2- temperat ure range 20-700 C. 3-round nozzle	27+ 1pcs FO C	680	18360
18	ALL-RE18-218	Add	Welding nozzle, round, two way, used for welding rods of different materials, diameter 3 mm. accessory for item T43.	pcs	756Y12=3	Welding Nozzle, round .	27+ 1pcs FO C	125	3375
19	ALL-RE18-219	Add	Welding nozzle, round, two way, used for welding rods of different materials, diameter 4 mm. accessory for item T43.	pcs	756Y12=4	Welding Nozzle, round .	24+ 1pcs FO C	125	3000
20	ALL-RE00-220	T 46	Sanding belt, for wood and plastic, length 2500 mm, width 50 mm, grit 120. (spare part for belt sander and disk sander machine).	set	649G14=250 X120	Sanding belt for 701P12/701P14/701P30=G	39+ 1set FO C	12	468
21	ALL-RE00-221	T 47	Sand paper disk, self adhesive, diameter 350 mm, grit 40.(spare part for sander and disk sander machine).	pcs	649P8=350X 40	Sand paper disk, self adhesive.	38+ 1pcs FO C	13	494
22	ALL-RE00-222	T 50	T-handled hexagon wrench, steel with plastic handle. Wrench size 2 mm.	pcs	709S15=2	T-handled hexagon wrench, steel with plastic with plastic handle .wrench size 2 mm	126 + 2pcs FO C	6	756
23	ALL-RE00-223	T 51	T-handled hexagon wrench, steel with plastic handle. Wrench size 3 mm.	Pcs	709S15=3	T-handled hex Wrench	120 + 2pcs FO C	6	720
24	ALL-RE00-224	T 52	T-handled hexagon wrench, steel with plastic handle. Wrench size 4mm.	Pcs	709S15=4	T-handled hex Wrench	161 + 2pcs FO C	6	966

25	ALL-RE00-225	T 53	T-handled hexagon wrench, steel with plastic handle. Wrench size 5 mm.	pcs	709S15=5	T-handled hexagon wrench, steel with plastic with plastic handle .wrench size 5 mm	143 + 2pcs FO C	7	1001
26	ALL-RE18-226	Add	T- handled hexagon wrench, steel with plastic handle. Wrench size 8 mm.	pcs	709S15=8	T-handled hexagon wrench, steel with plastic with plastic handle .wrench size 8 mm	59+ 1pcs FO C	8	472
27	ALL-RE18-227	Add	T- handled hexagon wrench, steel with plastic handle. Wrench size 10 mm.	pcs	709S15=10	T-handled hexagon wrench, steel with plastic with plastic handle .wrench size 10 mm	64+ 1pcs FO C	8	512
28	ALL-RE00-230	T 67	Teflon sheet, width 1300-1600 mm, thickness 0.22 mm. sevice part for oven.	meter	759Y22=3	Teflon sheet, width 1300-1600 mm, thickness 0.22 mm. sevice part for oven .	176 + 2 meter FO C	180	31680
29	ALL-RE00-232	T 75	Inside funnel circumference gauge, used for measuring inside diameter of prosthetic foam cover.	pcs	743E5=1	Inside Circumference Gauge .	52	750	39000
30	ALL-RE00-234	T 77	Two channel vacum pipe, diameter 25 mm.	pcs	755R11	Two Channel Vacuum Pipe.	21+ 1pcs FO C	139	2919
31	ALL-RE00-236	T 93	Teflon tape used as accessory for hand sealing iron, width 80-100 mm.	meter	699Y2	Teflon sheet .	33+ 1meter FO C	8	264
32	ALL-RE00-237	T 99	Casting apparatus used for functional casting under wieght for different levels of lower limb stump, include base plate and a kit of plastic acceptance rings.	pcs	743A11	Otto bock Casting Apparatus .	38+ 1pcs FO C	2750	104500
33	ALL-RE18-238	Add	Casting rings, set of 4 piceses inside diameter 103 , 113, 126, 135 mm. plastic, used with the apparatus in item T99.	set	743A13=S	Casting rings, set of 4 piceses inside diameter 103, 113,126,135 mm,	37	120	4440

						plastic, used, with the apparatus in item T99.			
34	ALL-RE00-239	T 100	Casting platform used for weight bearing casting of knee or hip disarticulation, with two pices blocks. Used as accessories with item number 99.	pcs	743Y25	Casting platform used for weight bearing of knee or hip disarticulation, with two pices block. Used as accessories with item number 99.	29+1pcs FOC	325	9425
35	ALL-RE00-240	T 101	Pneumtic supported ischium trochenteric plaster casting apparatus, provides functional casting of ischial containment sockets while bearing weight. The pneumatic unit can be directly connected to the compressed air supply system. Used with the casting apparatus in item T99. include set of supported ischium trochenteric cast casting forms	pcs	743G10	Pneumatic SIT-Cast Plaster Ca. Apparatus .	18	6615	119070
36	ALL-RE00-241	T 103	Supported ischium trochenteric cast casting forms, right and left, all sizes, used with item T 101.	pcs	743Y50=11	SIT Casting Forms	22	236	5192
37	ALL-RE00-242	T 123	Pipe vise, with workbench holder, rotates and telescopes.	pcs	704G12	Pipe vise,with workbench holder, rotates and telescopes.	72	963	69336
38	ALL-RE00-243	T 124	Pipe vise, with workbench holder, swivels horizontally and ventrically, total height (without clamping lever)225-250mm.	pcs	704G300	Clamping Device	73	706	51538
39	ALL-RE00-244	T 152	Belt used as spare part for belt sanders machine, length 1400 mm, width 17 mm.	pcs	702P2=1.450	Belt used as spare part for belt sanders machine, length 1400 mm, width 17 mm.	41	65	2665
40	ALL-RE00-245	T 161	Fir cone miller, spiral toothed , length 75 mm, largest diameter 28 mm, thread diameter M 16 mm. stainless steel, for processings plastic.	pcs	729S24=M16	Conical Cutter.	71	190	13490
41	ALL-RE00-246	T 162	Fir cone miller, fine rasp stroke , length 75 mm, largest diameter 28 mm, thread diameter M 16 mm. stainless steel, for processing light metal and plastic.	pcs	729W23=M16	Conical Cutter.	49	293	14357
42	ALL-RE00-247	T 165	Sanding drum, conical shape, with rubber body, length 60 mm, diameter 36/22. thread M 16 mm.	pcs	749Z9=M16	Conical Sanding Drum .	44+1pcs	72	3168

			service part for milling machine.				FO C		
43	ALL-RE00-248	T 168	Sanding sleeve for sanding drum in item T165, grit 40	pcs	749Y26=40	Sanding sleeve	175 + 2pcs FO C	5	875
44	ALL-RE18-249	Add	Sanding sleeve for sanding drum in item T165, grit 80	pcs	74Y26=80	Sanding sleeve	156 + 2pcs FO C	5	780
45	ALL-RE00-250	T 170	Abrasive flap wheel used for final grinding and polishing painted surfaces of prosthesis shaft and all plastic.thread M 16 mm, service part for milling machine.	pcs	749Z11=5/8	Abrasive Buffing Tool	35	222	7770
46	ALL-RE00-251	T 173	Steel wire sanding drum, for processing foam cover, bore diameter 16 mm.	pcs	749P1=250	Wire wheel	37	102	3774
47	ALL-RE18-252	Add	Threaded connector with two fitting disks and a tensioning screw, for attaching the above sanding drum in item T173., thread diameter M 16 mm.	pcs	749Y20=M16	Threaded Connector	35	105	3675
48	ALL-RE00-253	T 174	Sanding belt, for wood and plastic, length 1650 mm, width 40 mm, grit 24. (spare part for belt sander and disk sander machine)	pcs	649G15=1650X40X24	Sanding Belts, endless	54+ 1pcs FO C	11	594
49	ALL-RE00-254	T 175	Sanding belt, for wood and plastic, length 1480 mm, width 100 mm, grit 24. (spare part for belt sander and disk sander machine).	pcs	649G15=1480X100X24	Sanding Belts, endless	71+ 1pcs FO C	18	1278
50	ALL-RE00-255	T 176	Sanding belt, for wood and plastic, length 1650 mm, width 40 mm, grit 60. (spare part for belt sander and disk sander machine).	pcs	649G15=1650X40X60	Sanding Belts, endless	143	11	1573
51	ALL-RE00-256	T 177	Sanding belt, for wood and plastic, length 1480 mm, width 100 mm, grit 60. (spare part for belt sander and disk sander machine).	pcs	649G15=1480X100X60	Sanding Belts, endless	157	21	3297
52	ALL-RE00-259	T 220	Two channel vacuum pipe, diameter 48 mm.	pcs	755R2	Two channel vacuum pipe, straight	26+ 1pcs FO C	115	2990
53	ALL-RE00-260	T230	Silicone Parting Agent Spray, used for parting , gliding and lubricating.	pcs	519L5	Silicon parting Agent	38+ 1pcs FO C	26	988
54	ALL-RE00-261	T240	Riveting bar, steel ,used to fix rivet.	pcs	73515=1	Riveting Bar	23+ 1pcs FO C	560	12880
55	ALL-RE00-262	T254	Revolving hole punch pliers, steel, punching tube diameter 2, 2.5 ,3, 3.5 , 4, 5 mm. with reopening spring between holders.	pcs	706L1	Revolving Hole punch	36+ 1pcs FO C	79	2844

56	ALL-RE18-263	Add	Lapping Roller, thread diameter M 16 mm, width 80 mm, used as service part for milling machine.	pcs	702L78=60	Cloth Wheel	42	150	6300
57	ALL-RE18-264	Add	Body calipers used for measuring body segments, measurement range 600 mm.	pcs	743S1=60	Body Caliper	14+1pcs FOC	165	2310
58	ALL-RE18-268	Add	Electric cast cutter, straight shank, with oscillating blade, power/ 220-230 V.	pcs	756P12=23	Electric Cast cutter, straight	69	500	34500
59	ALL-RE18-271	Add	Hand sealing iron, power/ 220- 230 V.	pcs	756E1=220V	Hand Sealing Iron, 220 Volt	24+1pcs FOC	753	18072

١- شركة OTTOBOOCK بمنشأ (الماني - صيني - النمسا)

جدول رقم (٢) - حسابات شركة (Streifender) ومن منشأ (الماني) وحسب أحتياج عام (٢٠٢١) :

NO.	National Code	National Code	Item Discription	Unit	Streifender Code	Streifender Discription	Qty. 2021 (pcs)	Unit Price US D	Total price US D
1.	ALL-RE00-196	T 2	Surform replacement blad, half round, for fast shaping of plaster cast.	pcs	158P3/HR	Replcement blade for 158P2, half round	3148+ 32 pcs FOC	9	28332
2.	ALL-RE00-198	T 3	Surform replcement blad, round, for fast shaping of plaster cast.	pcs	158P3/R	Replcement blade for 158P2, round	1598+ 17pcs FOC	9	14382
3.	ALL-RE18-200	Add	Surform replcement blad, flat, for fast shaping of plaster cast.	pcs	158P3/F	Replcement blade for 158P2, flat	1211+ 13pcs FOC	9	10899
4.	ALL-RE00-202	T 7	Rasp (grinding) head, service part for grinding machine, used for processing wood, foam. medium rasp	pcs	161P5/2	Rasp Head, medium cut, 50X80 mm, M16	133+ 2pcs FOC	110	14630

			stroke, thread M 16, diameter 50 mm, length approx(60-100 mm), metal.						
5.	ALL-RE00-203	T 8	Sanding drum, made of rubber, service part for grinding machine to pull onto router machine shaft, outside diameter 72.5 mm, length 200 mm.	pcs	161P85/200	Sanding Roll, tapered hole, 200X75,5 mm	85+ 1pcs FOC	25	21 25
6.	ALL-RE00-204	T 9	Sanding sleeve used with the sanding drum above(T8), outside diameter 73mm, length 200 mm, grit 40.	pcs	161P86/40	Sanding sleeves, 200X72,5 mm, grit 40	303+ 4pcs FOC	7	21 21
7.	ALL-RE00-205	T 10	Sanding sleeve used with the sanding drum above(T8), outside diameter 73mm, length 200 mm, grit 80.	pcs	161P86/80	Sanding sleeves, 200X72,5 mm grit 80	187+ 2pcs FOC	6	11 22
8.	ALL-RE00-206	T 11	Sanding drum, service part for grinding machine, grinder made of rubber with metallic core, thread M 16, outside diameter 45 mm, length 70 mm.	pcs	161P72	Sanding Roll, small, 45X75 mm, M16	31+ 1pcs FOC	110	34 10
9.	ALL-RE00-207	T 12	Sanding drum, service part for grinding machine, grinder made of rubber with metallic core, thread M 16, outside diameter 60 mm, length 70 mm.	pcs	161P73	Sanding Roll, small, 60X75 mm, M16	31 + 1pcs FOC	135	41 85
10.	ALL-RE00-208	T 13	Sanding sleeve, used for sanding drum in item T11, outside diameter 45 mm, length 70, grit 40.	pcs	161P72/40	Sanding sleeves, 45X75 mm, grit 40	182 + 2pcs FOC	4	72 8
11.	ALL-RE00-209	T 14	Sanding sleeve, used for sanding drum in item T12, outside diameter 60 mm, length 70, grit 80.	pcs	161P73/80	Sanding sleeves, 60X75 mm, grit 80	158+ 2pcs FOC	4	63 2

12.	ALL-RE00-212	T 18	Sanding drum, service part for grinding machine, drum made of rubber(cap or arbor shap) with metallic core, thread M 16, outside diameter 45 mm, length70 mm.	pcs	161P40/45	Sanding Drum, 45X70 mm, M16	31 + 1pcs FOC	140	43 40
13.	ALL-RE00-213	T 19	Sanding drum, service part for grinding machine, drum made of rubber(cap or arbor shap) with metallic core, thread M 16, outside diameter (60-65 mm), length 90mm.	pcs	161P40/60	Sanding Drum, 65X90 mm, M16	33 + 1pcs FOC	150	49 50
14.	ALL-RE00-217	T 43	Hot air gun , technical data : 1- power/ 220-230 V. 2- temperature range 20-700 C . 3-round nozzle.	pcs	168P40/1523	Hot Air Blower "TRIAC ST" , 230 V	28 + 1pcs FOC	680	19 04 0
15.	ALL-RE18-218	Add	Welding nozzle, round, two way, used for welding rods of different materials, diameter 3 mm. accessory for item T43.	pcs	168P410/3	Welding Nozzle for 168P40, 3 mm	28 + 1pcs FOC	125	35 00
16.	ALL-RE18-219	Add	Welding nozzle, round, two way, used for welding rods of different materials, diameter 4 mm. accessory for item T43.	Pcs	168P410/4	Welding Nozzle for 168P40, 4 mm	25 + 1pcs FOC	125	31 25
17.	ALL-RE00-220	T 46	Sanding belt, for wood and plastic, length 2500 mm, width 50 mm, grit 120. (spare part for belt sanderand disk sander machine).	pcs	107P63/120	Grinding Belt, 2500x50 mm, grit 120	40+ 1pcs FOC	12	48 0
18.	ALL-RE00-221	T 47	Sand paper disk, self adhesive, diameter 350 mm, grit 40.(spare part for sander and disk sander machine).	pcs	107P30/350	Sanding Disc, Ø 350 mm, grit 36	39 + 1pcs FOC	13	50 7
19.	ALL-RE00-222	T 50	T-handled hexagon wrench,	pcs	173P3/2	T-Handle Hex Wrench, 2 mm	126 + 2pcs FOC	6	75 6

			steel with plastic handle. Wrench size 2 mm.						
20.	ALL-RE00-223	T 51	T-handled hexagon wrench, steel with plastic handle. Wrench size 3 mm.	pcs	173P3/3	T-Handle Hex Wrench, 3 mm	121+ 2pcs FOC	6	72 6
21.	ALL-RE00-224	T 52	T-handled hexagon wrench, steel with plastic handle. Wrench size 4mm.	pcs	173P3/4	T-Handle Hex Wrench, 4 mm	161 + 2pcs FOC	6	96 6
22.	ALL-RE00-225	T 53	T-handled hexagon wrench, steel with plastic handle. Wrench size 5 mm.	pcs	173P3/5	T-Handle Hex Wrench, 5 mm	143+ 2pcs FOC	7	10 01
23.	ALL-RE18-226	Add	T- handled hexagon wrench, steel with plastic handle. Wrench size 8 mm.	pcs	173P3/8	T-Handle Hex Wrench, 8 mm	59 + 1pcs FOC	8	47 2
24.	ALL-RE18-227	Add	T- handled hexagon wrench, steel with plastic handle. Wrench size 10 mm.	pcs	173P3/10	T-Handle Hex Wrench, 10 mm	64 + 1pcs FOC	8	51 2
25.	ALL-RE00-228	T 55	Rivet header, with flat head shape, steel, for rivet diameter 4 mm.	pcs	162P5/4	Rivet Header, 4 mm	67 + 1pcs FOC	15	10 05
26.	ALL-RE00-230	T 67	Teflon sheet, width 1300-1600 mm, thickness 0.22 mm. sevice part for oven.	meter	119P18	PTFE-Film, 1525X0.35 mm	49 + 1pcs FOC	180	88 20
27.	ALL-RE00-233	T 76	Hip leveling guide, for determination of the hip tilt.	pcs	165P13	Pelvic Level for determination of the hip tilt, 330 mm	52 + 1pcs FOC	250	13 00 0
28.	ALL-RE00-234	T 77	Two channel vacum pipe, diameter 25 mm.	pcs	168P60	Two Way suction pipe, zinc plated, 400x25 mm	22 + 1pcs FOC	139	30 58
29.	ALL-RE00-235	T 78	Two channel vacum pipe, diameter 34 mm.	pcs	168P61	Two Way suction pipe, zinc plated, 400x33 mm	50 + 1pcs FOC	105	52 50
30.	ALL-RE00-236	T 93	Teflon tape used as accessory for hand sealing iron, width 80-100 mm.	meter	119P22	PTFE Tape, 100 x 0.13 mm	33 + 1pcs FOC	8	26 4
31.	ALL-RE00-247	T 165	Sanding drum, conical shape, with rubber body, length 60 mm, diameter 36/22. thread M 16 mm. service part for milling machine.	pcs	161P80	Sanding Drum, conical, M16	45 + 1pcs FOC	72	32 40
32.	ALL-RE00-248	T 168	Sanding sleeve for sanding	pcs	107P1/50	Sanding sleeves, conical, grit 50	176 + 2pcs FOC	5	88 0

			drum in item T165, grit 40						
33.	ALL-RE18-249	Add	Sanding sleeve for sanding drum in item T165, grit 80	pcs	107P1/80	Sanding sleeves, conical, grit 80	156 + 2pcs FOC	5	780
34.	ALL-RE00-253	T 174	Sanding belt, for wood and plastic, length 1650 mm, width 40 mm, grit 24. (spare part for belt sander and disk sander machine).	pcs	107P53/24	Sanding Belt, endless, 1650X40 mm, grit 24	55 + 1pcs FOC	11	605
35.	ALL-RE00-254	T 175	Sanding belt, for wood and plastic, length 1480 mm, width 100 mm, grit 24. (spare part for belt sander and disk sander machine).	pcs	107P52/24	Sanding Belt, endless, 1480X100 mm, grit 24	71 + 1pcs FOC	18	1278
36.	ALL-RE00-259	T 220	Two channel vacum pipe, diameter 48 mm.	pcs	168P62	Two Way Suction Pipe, zinc plated, 540x48 mm	26 + 1pcs FOC	115	2990
37.	ALL-RE00-260	T230	Silicone Parting Agent Spray, used for parting , gliding and lubricating.	pcs	116P11	Sillicone Parting Agent Spray, 400 ml	38 + 1pcs FOC	26	988
38.	ALL-RE00-261	T240	Riveting bar, steel ,used to fix rivet.	pcs	164P18	Riveting Bar, with rivet-hole, forged metal, 680 mm length	24 + 1pcs FOC	560	13440
39.	ALL-RE00-262	T254	Revolving hole punch pliers, steel, punching tube diameter 2, 2.5 ,3, 3.5 , 4, 5 mm. with reopening spring between holders.	pcs	165P1	Revolving Hole Punch, 240 mm	36 + 1pcs FOC	79	2844
40.	ALL-RE18-264	Add	Body calipers used for measuring body segments, measurement range 600mm.	pcs	16P18/600	Body Caliper "Streifeneder" , 600 mm	14 + 1pcs FOC	165	2310
41.	ALL-RE18-265	Add	Conical drill, tapered, used for peeling plastic (for valve holes), diameter 8-20 mm	pcs	151P5/820	Peeling Drill, tapered, HSS 4-20 mm CIP	86 + 1pcs FOC	165	14190
42.	ALL-RE18-269	Add	Circular saw blade, diameter 65mm, used for the above electric cast cutter.	pcs	159P4/65	Circular Saw Blade, 65 mm	498 + 6 pcs FOC	7	3486
43.	ALL-RE18-270	Add	Segment saw blade, diameter 65mm, used for	pcs	159P8	Segmented Saw Blade for 168P 23	397 + 5 pcs FOC	7	2779

			the above electric cast cutter						
44.	ALL- RE18-271	Add	Hand sealing iron, power/ 220- 230 V.	pcs	168P5	Hot Sealing Iron, 230 V / 50 Hz / 1 Ph/ 0.2 kw	9 + 1pcs FOC	753	67 77